

**Specifiche tecniche:**

Nom. voltage V	Power 10 min 1.60 Vpc 25°C W/block	Nominal capacity C <sub>10</sub> 1.80 Vpc 25°C Ah	Length (l) max. mm	Width (b/w) max. mm	Height (h1) max. mm	Height incl. connectors (h2) max. mm	Weight approx. kg	Internal resistance mOhm*	Short circuit current A*	Terminal
12	3040	92.8	309	172	223	239	31.0	5.20	2425	F-M6


**Scarica a corrente costante in A (25°C):**

Vpc	3 min	5 min	10 min	15 min	20 min	30 min	45 min	1h	2h	3h	5h	8h	10h
1,90	195	195	195	176	138	94,2	70	56,7	33,5	24,8	15,7	10,1	8,21
1,85	209	209	209	180	147	107	78,8	63,1	36,3	26,6	16,9	11	8,94
1,80	271	271	229	187	153	116	84,1	66,9	37,8	27,4	17,5	11,4	9,28
1,75	307	307	240	202	163	120	87	68,9	38,6	27,8	17,8	11,5	9,41
1,70	342	342	250	209	168	123	88,5	70,1	39,1	28,1	17,9	11,6	9,49
1,65	373	373	260	210	169	124	89,6	70,8	39,4	28,3	18	11,7	9,56
1,60	399	399	268	212	171	126	90,5	71,5	39,7	28,5	18,2	11,8	9,61

**Scarica a potenza costante in W/Block (25°C):**

Vpc	3 min	5 min	10 min	15 min	20 min	30 min	45 min	1h	2h	3h	5h	8h	10h
1,90	2250	2250	2250	2090	1653	1120	841	683	405	302	193	125	101
1,85	2830	2830	2440	2170	1741	1260	928	747	434	320	205	133	108
1,80	3180	3180	2550	2200	1799	1340	983	786	450	328	210	137	111
1,75	3500	3500	2680	2260	1855	1390	1010	807	458	332	212	138	113
1,70	3780	3780	2790	2310	1897	1420	1020	818	462	334	214	139	114
1,65	4010	4010	2870	2330	1909	1430	1030	825	465	336	216	140	114
1,60	4180	4180	3040	2350	1914	1440	1040	830	467	337	218	141	115

**Terminale:**



11 Nm

**Disegno:**

